

Application

- ✓ Low-tension electric wire for Automobiles.
- ✓ Used in Motorcycles and other motor vehicles for starting, charging, lighting, signal and instrument panel circuits.

Product Construction

- ✓ Conductor : Soft-annealed electrolytic Copper E-Cu ETP1 according to DIN 13602, bare conductor (Symmetrical)
- ✓ Insulation : PA (Polyamide) (Thin wall)
- ✓ Colour : As per customer order.
- ✓ Single core

Technical Data


- ✓ Temperature Range : - 40°C to +105°C (3000 Hours)
- ✓ Test Voltage: 3kV (r.m.s.) for cables < 0.5 mm² 5kV (r.m.s.) for cables ≥ 0.5 mm²
- ✓ FL : Automotive cable
- ✓ R : Reduced wall thickness
- ✓ 4Y : polyamide
- ✓ A : Symmetrical (Structure A)
- ✓ Standard : ISO 6722, Class B

Features

- ✓ Flame retardant
- ✓ Highly resistant against acids, lyes, Petrol and diesel.
- ✓ Type of flexibility.
- ✓ Fuel resistance

Automotive Cables **FLR4Y-A**

2D View



Approvals Accreditations Certifications



Part Number	Conductor Construction				Insulation Wall Thickness Min.	Cable		Current Carrying Capacity	Max. Conductor Resistance at 20°C	Standard Length*
	Nominal Cross-Section	No. of Strands	Diameter of Single wire max.	Conductor Diameter Max.		Overall Diameter Max.	Weight Approx.			
	mm ²	nos.	mm	mm	mm	mm	kg/km	Amps	Ω/km	mtrs
A87605XX*	0.35	7	0.27	0.90	0.20	1.3	4	10	54.4	500
A87606XX	0.5	19	0.19	1.10	0.22	1.6	6	13	37.1	500
A87608XX	0.75	19	0.24	1.30	0.24	1.9	9	18	24.7	500
A87610XX	1	19	0.27	1.50	0.24	2.1	11	21	18.5	500
A87613XX	1.5	19	0.33	1.80	0.24	2.4	16	27	12.7	500
A87616XX	2.5	37	0.28	2.20	0.28	3.0	26	38	7.60	500

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

- ✓ Current Carrying capacity given is for the maximum conductor operating temperature of 105°C and ambient air temperature of 40°C.
- ✓ * Other length as per Customer order.

** We have obtained various approvals, accreditations, and certifications — some of which may not be relevant to this catalog.



www.siechem.com