

Application

- ✓ Low-tension electric wire for Automobiles.
- ✓ Used in Motorcycles and other motor vehicles for starting, charging, lighting, signal and instrument panel circuits.
- ✓ Especially used for circuits requiring heat resistance.

Features

- ✓ Flame retardant.
- ✓ Highly resistant against acids, alkaline, petrol and diesel.
- ✓ Extra flexibility.
- ✓ RoHS.

Product Construction


- ✓ Conductor : Tinned copper conductor, Asymmetrical Structure B.
- ✓ Insulation : PFA (Reduced wall thickness).
- ✓ Color : As per customer order.

Technical Data

- ✓ Temperature Range : -40°C to 200°C / 3000hrs.
- ✓ Voltage : 60V.
- ✓ Min. Bending radius : 5xCable OD.
- ✓ FL : Automotive cables.
- ✓ R : Reduced wall thickness.
- ✓ 51Y : Perfluoroalkoxy copolymer (PFA).
- ✓ Sn : Tinned copper conductor.
- ✓ Standard: ISO 19642-3.

**Automotive
Cables**
FLR51Y Sn-B

2D View



Approvals Accreditations Certifications



**

Part Number	Conductor Construction				Insulation Wall Thickness Min.	Cable Overall Diameter		Weight Approx.	Max. Conductor Resistance at 20°C	Current Carrying Capacity	Standard Length*
	Nominal Cross-Section	No. of Strands	Diameter of Single wire Max.	Conductor Diameter Max.		Min.	Max.				
	mm ²	nos.	mm	mm	mm	mm	mm	kg/km	Ω/km	Amps	mtrs
D19405XX	0.35	12	0.21	0.90	0.20	1.20	1.40	5	55.5	14	500
D19406XX	0.50	16	0.21	1.10	0.22	1.40	1.60	7	38.2	18	500
D19408XX	0.75	24	0.21	1.30	0.24	1.70	1.90	9	25.4	24	500
D19410XX	1.00	32	0.21	1.50	0.24	1.90	2.10	13	19.1	29	500
D19413XX	1.50	30	0.26	1.80	0.24	2.20	2.40	17	13.0	37	500
D19416XX	2.50	50	0.26	2.20	0.28	2.70	3.00	28	7.82	52	500
D19419XX	4.00	56	0.31	2.80	0.32	3.40	3.70	45	4.85	70	500
D19423XX	6.00	84	0.31	3.40	0.32	4.00	4.30	63	3.23	95	500

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

- ✓ * Other length as per Customer order.
- ✓ Current Carrying capacity given is for the maximum conductor operating temperature of 260°C and ambient temperature of 40°C.
- ✓ ** We have obtained various approvals, accreditations, and certifications — some of which may not be relevant to this catalog.



www.siechem.com