



Application

- ✓ Low-tension electric wire for Automobiles.
- ✓ Used in Motorcycles and other motor vehicles for starting, charging, lighting, signal and instrument panel circuits.
- ✓ Especially used for circuits requiring heat resistance.

Product Construction

- ✓ Conductor : Tinned copper conductor, Asymmetrical Structure B.
- ✓ Insulation : FEP (Reduced wall thickness).
- ✓ Color : As per customer order.

Technical Data


- ✓ Temperature Range : -40°C to 200°C / 3000hrs.
- ✓ Voltage : 60V.
- ✓ Min. Bending radius : 5xCable OD.
- ✓ FL : Automotive Cables.
- ✓ R : Reduced wall thickness.
- ✓ 6Y : Fluorinated Ethylene Propylene (FEP).
- ✓ Sn : Tinned copper conductor.
- ✓ A6 : Class F.
- ✓ Standard: ES-AU5T-1A348-AA.

Features

- ✓ Flame retardant.
- ✓ Highly resistant against acids, alkaline, petrol and diesel.
- ✓ Extra flexibility.
- ✓ RoHS.

**Automotive
Cables**
FLR6Y Sn-A6-TBE

2D View



Approvals Accreditations Certifications



Part Number	Conductor Construction				Insulation Wall Thickness Min.	Cable Overall Diameter		Weight Approx.	Max. Conductor Resistance at 20°C	Current Carrying Capacity	Standard Length*
	Nominal Cross-Section	No. of Strands	Diameter of Single wire Max.	Conductor Diameter Max.		Min.	Max.				
	mm ²	nos.	mm	mm	mm	mm	mm	kg/km	Ω/km	Amps	mtrs
D27605XX	0.35	12	0.21	0.90	0.20	1.20	1.40	5	55.5	14	500
D27606XX	0.50	16	0.21	1.10	0.22	1.40	1.60	7	38.2	18	500
D27608XX	0.75	24	0.21	1.30	0.24	1.70	1.90	9	25.4	24	500
D27610XX	1.00	32	0.21	1.50	0.24	1.90	2.10	13	19.1	29	500
D27613XX	1.50	30	0.26	1.80	0.24	2.20	2.40	17	13.0	37	500
D27614XX	2.00	28	0.38	2.00	0.28	2.50	2.80	23	9.69	50	500
D27616XX	2.50	50	0.30	2.20	0.28	2.70	3.00	28	7.82	52	500
D27617XX	3.00	44	0.34	2.40	0.32	3.10	3.40	35	6.36	64	500
D27619XX	4.00	56	0.38	2.80	0.32	3.40	3.70	42	4.85	70	500

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

- ✓ * Other length as per Customer order.
- ✓ Current Carrying capacity given is for the maximum conductor operating temperature of 200°C and ambient temperature of 40°C.
- ✓ ** We have obtained various approvals, accreditations, and certifications — some of which may not be relevant to this catalog.


www.siechem.com