

**Application**

- ✓ Low-tension electric wire for automobiles.
- ✓ Used in motorcycles and other motor vehicles for starting, charging, lighting, signal and instrument panel circuits.

**Product Construction**

- ✓ Conductor : Annealed Tinned Flexible Copper (Symmetrical Structure A) Conductor construction according to ISO 6722-1
- ✓ Insulation : ETFE ( Ethylene tetrafluoroethylene) with properties according to ISO 6722-1 Class E
- ✓ Colour : As per customer order.
- ✓ Single core

**Technical Data**


- ✓ Temperature Range : - 60°C to +180°C (3000 Hours)
- ✓ Test Voltage 3kV (r.m.s.) for cables < 0.5 mm<sup>2</sup>  
5kV (r.m.s.) for cables ≥ 0.5 mm<sup>2</sup>
- ✓ Standard ISO 6722-1 Class E (Thin Wall)
- ✓ Voltage 60V

**Features**

- ✓ Flame retardant.
- ✓ Highly resistant against acids, lyes, petrol and diesel.
- ✓ Good mechanical & thermal properties.
- ✓ Excellent chemical resistance.
- ✓ Extra flexibility.
- ✓ Class E Compliant.

Automotive Cables **FLR7Y-A**

**2D View**



**Approvals | Accreditations | Certifications**



Part Number	Conductor Construction				Insulation Wall Thickness Nom.	Cable		Current Carrying Capacity	Max. Conductor Resistance at 20°C	Standard Length*
	Nominal Cross-Section	No. of Strands	Diameter of Single wire Max.	Conductor Diameter Max.		Overall Diameter Max.	Weight Approx.			
	mm <sup>2</sup>	nos.	mm	mm	mm	mm	kg/km	Amps	Ω/km	mtrs
C29305XX*	0.35	7	0.27	0.90	0.25	1.3	6	13	55.5	1000
C29306XX	0.5	19	0.19	1.10	0.28	1.6	8	18	38.2	1000
C29308XX	0.75	19	0.24	1.30	0.30	1.9	12	23	25.4	1000
C29310XX	1	19	0.27	1.50	0.30	2.1	14	28	19.1	1000
C29313XX	1.5	19	0.33	1.80	0.30	2.4	20	36	13.0	1000
C29316XX	2.5	19	0.41	2.20	0.35	3.0	31	50	7.82	1000

Note : XX\* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

- ✓ Current Carrying capacity given is for the maximum conductor operating temperature of 180°C and ambient air temperature of 40°C.
- ✓ \* Other length as per Customer order.



www.siechem.com