

Application

- ✓ Low-tension electric wire for Automobiles.
- ✓ Used in Motorcycles and other motor vehicles for starting, charging, lighting, signal and instrument panel circuits.

Product Construction

- ✓ Conductor : Soft-annealed electrolytic Copper E-Cu ETP1 according to DIN EN 13602, bare conductor
- ✓ Insulation : Soft PVC Cold resistant
- ✓ Colour : As per customer order.
- ✓ Single core

Technical Data


- ✓ Temperature Range : - 50°C to +105°C (3000 Hours)
- ✓ Test Voltage: 3kV (r.m.s.) for cables < 0.5 mm² 5kV (r.m.s.) for cables ≥ 0.5 mm²
- ✓ FL : Automotive cable
- ✓ R : Reduced wall thickness
- ✓ YK : Cold resistant PVC
- ✓ Standard : Bosch 5998 342.

Features

- ✓ Cold resistant
- ✓ Highly resistant against acids, lyes, Petrol and diesel.
- ✓ Flexible conductors with PVC thick wall insulation

Automotive Cables **FLRYK**

2D View



Approvals Accreditations Certifications



Part Number	Conductor Construction				Insulation Wall Thickness Nom.	Cable		Current Carrying Capacity	Max. Conductor Resistance at 20°C	Standard Length*
	Nominal Cross-Section	No. of Strands	Diameter of Single wire max.	Conductor Diameter Nom.		Overall Diameter Max.	Weight Approx.			
	mm ²	nos.	mm	mm	mm	mm	kg/km	Amps	Ω/km	mtrs
A88406XX*	0.5	16	0.21	1.00	0.22	1.6	7	13	37.1	500
A88410XX	1	32	0.21	1.40	0.30	2.1	12	21	18.5	500
A88413XX	1.5	30	0.26	1.70	0.24	2.4	17	27	12.7	500
A88416XX	2.5	50	0.26	2.10	0.70	3.7	33	39	7.6	500

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

✓ Current Carrying capacity given is for the maximum conductor operating temperature of 105°C and ambient air temperature of 40°C.

✓ * Other length as per Customer order.

** We have obtained various approvals, accreditations, and certifications — some of which may not be relevant to this catalog.



www.siechem.com