

Thermosetting Insulated, Single core, Sheathed Fire Resistant Cable, 450/750 V

Application

- ✓ Metro Rail, Airport, Schools, Shopping malls, Cinemas, High-rise Buildings and fire prone areas.
- ✓ Indoor and Outdoor uses.

Product Construction

- ✓ Conductor : Annealed Copper conductor, Class 2 Stranded conductor.
- ✓ Insulation 1 : Glass Mica tape
- ✓ Insulation 2 : EBXL-XLPE-120°C.
- ✓ OuterSheath : XLPO

Technical Data

- ✓ Temperature Range :-15°C to + 120°C
- ✓ Rated Voltage (U₀/U) : 450/750 V
- ✓ Test Voltage : 3.5kV/5 min
- ✓ Bending Radius (Min) :Upto 8 X cable OD
- ✓ Specification : BS 7211,Table - 5

Features

- ✓ Flammability : IEC 60332-1 & IEC 60332-3 Categories A, B & C
- ✓ Resistance to Fire : CWZ of BS : 6387, IEC 60331 & F-2 of BS : 7846
- ✓ Smoke Emission : IEC 61034 - 1 & 2
- ✓ Acid Gas Content : IEC 60754 -1 & 2, BS EN 50267 - 1 & 2
- ✓ **Special Features :**
 - a) Maintains Circuit Integrity for 3 hours under fire condition.
 - b) Zero Halogen, Low Smoke and Resistance to flame propagation.
 - c) Siechem Fire Resistant Cable meets BS 7846 Cat F2 and meets Test requirements as per BS 6387 CWZ, at an enhanced voltage of 600/1000V.
 - d) Siechem Fire Resistant Cable also meets 60 minute rating (PH60) to BS EN 50200 and a 30 minute rating to BS 8434-1. These tests demonstrate that Fire Resistant Cable also meets the requirements for use in "Standard" installations in accordance with BS 5839-1 : 2002 for fire detection and alarm systems, and Cables with inherently high resistance to attack by fire in accordance with BS 5266-1 : 2005 for emergency lighting.

Approvals	Accreditations	Certifications

Part Number	Number of Cores and mm ² Per Conductor	Conductor Construction	Outer Diameter in mm approx.		Weight Kg/Km approx.
			Min	Max	
73010XX	1C x 1	7 X 0.44	4.0	4.9	39
73013XX	1C x 1.5	7 X 0.53	4.3	5.2	46
73016XX	1C x 2.5	7 X 0.67	4.7	5.6	59
73019XX	1C x 4	7 X 0.85	5.3	6.4	80
73023XX	1C x 6	7 X 1.04	5.9	7.1	104
73027XX	1C x 10	7 X 1.35	6.7	8.1	149
73028XX	1C x 16	7 X 1.7	7.6	9.2	220
73030XX	1C x 25	7 X 2.14	9.4	11.4	327
73032XX	1C x 35	7 X 2.52	10.6	12.8	436

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

** We have obtained various approvals, accreditations, and certifications — some of which may not be relevant to this catalog.



www.siechem.com