

Siechem UL 2598 APC, PVC Insulated 60°C, 300 V AC Cable

Application

- ✓ Appliance wiring
- ✓ Internal wiring of meters, panels, electrical and electronic equipment.

Product Construction

- ✓ Conductor : Annealed Solid / Stranded Bare Copper (Tinning on request).
- ✓ Insulation : PVC
- ✓ Shield : Optional
- ✓ Jacket : PVC
- ✓ Colour : As per customer order.

Technical Data


- ✓ Temperature Range : +60°C
- ✓ Voltage Rating : 300 V AC

Features

- ✓ Flame retardant
- ✓ Resistant to water, oil, acids, solvents and fungus.

UL Cables **2598**

2D View



Approvals	Accreditations	Certifications

Part Number	Conductor Construction			Insulation Wall Thickness Nom.	Outer Sheath Thickness Nom.	Cable		Max. Conductor Resistance at 20°C
	Number of Cores	Conductor Size	No. of Strands / Wire dia			Overall Diameter Max.	Weight Approx.	
	Nos.	AWG	nos. / mm	mm	mm	mm	kg/km	Ω/km
P4328104	4	18	19/0.234	0.43	0.80	6.80	77.30	21.8
P4328105	5	18	19/0.234	0.43	0.84	7.48	98.91	21.8
P4328107	7	18	19/0.234	0.43	0.94	8.33	125.00	21.8
P4328109	9	18	19/0.234	0.43	0.94	10.05	166.79	21.8
P4328112	12	18	19/0.234	0.43	1.02	10.98	211.17	21.8
P4328115	15	18	19/0.234	0.43	1.14	12.38	265.75	21.8
P4328119	19	18	19/0.234	0.43	1.14	13.03	315.87	21.8
P4328125	25	18	19/0.234	0.43	1.52	15.94	443.30	21.8
P4327802	2	12	19/0.47	0.8	0.80	9.61	118.06	5.43
P4327804	4	12	19/0.47	0.8	0.80	11.29	208.92	5.43

Note : XX* : Please add last two digits in the part number as per the colour code given hereunder replacing XX while ordering.

Red - 01	Yellow - 02	Blue - 03	Black - 04	Green - 05	Yellow-Green - 06	Grey - 07	Brown - 08	White - 09	Orange - 10	Violet - 11
Chocolate - 12	Tan - 13	Charcoal - 14	LT Blue - 15	DK Grey - 16	LT Green - 17	DK Green - 18	DK Blue - 19	Purple - 20	Pink - 21	

** We have obtained various approvals, accreditations, and certifications — some of which may not be relevant to this catalog.

